



Sheng Da Cable CO., Ltd

Profibus Dp 电缆

- 退火软铜导体
- 对绞发泡聚乙烯绝缘
- 铝箔/ PET屏蔽
- 镀锡铜线编织屏蔽
- PVC护套

退火软铜导体

铝箔/ PET屏蔽

PVC护套



镀锡铜线编织屏蔽

CABLE SPECIFICATION

CUSTOMER'S P/N	Profibus DP 1x2x22AWG	CUSTOMER	FILE N.O.	
DESCRIPTION	22 AWG copper conductors, foam PE insulation, twisted pairs, overall shield (100% coverage) plus a tinned copper braid (65% coverage), PVC jacket.		DATE	22/06/2018
			VER	A
			PAGE	1/1

Item	DESCRIPTION	
INNER CONDUCTOR	MATERIAL	Bare Copper
	DIMENSIONS	0.64mm
INSULATION (twisted pairs)	MATERIAL	Foam Polyethylene
	DIMENSIONS	2.55mm
FIRST SHIELD (Tape)	MATERIAL	Aluminum/PET/ Aluminum -Foil Non-Bonded
	OVERALL SHIELD COVERAGE	100%
SECOND SHIELD (Braid)	MATERIAL	Tinned Copper Wire
	DIMENSIONS	0.110mm
	CONSTRUCTION	7×16
	Nom.Coverage	65%
DRAIN WIRE	MATERIAL	Tinned Copper Wire
	DIMENSIONS	0.25 mm x 7
JACKET	MATERIAL	RoHS-PVC
	DIMENSIONS	8.0mm

MECHANICAL SPECIFICATION

Operation Temperature Rating (°C)	-20 to +70
-------------------------------------	------------

ELECTRICAL SPECIFICATIONS (20°C)

Inner Conductor DC Resistance	≤55.00 Ω/km
Characteristic Impedance	150 Ω

佛山市顺德区盛大电缆有限公司

-- 中国工厂

中国广东省佛山市顺德区容桂街道高新技术
开发区昌宝西路100号

电话: 86-757-2638 9094

传真: 86-757-2662 5464

邮箱: Marketing@shengda-cable.com

香港迅发创科有限公司

-- 总公司

香港中环德辅道中272-284号兴业
商业中心8楼803室

电话: 852-2559 3968

传真: 852-2857 5506

邮箱: shunfat@shunfathk.com

浏览我们的网站:

www.shengda-cable.com/ch.php

